



P.O. Box 368, Union, NJ 07083-0368, 908-687-7810, 800-327-2443, Fax: 908-687-8860

985135

January 11, 2002

985135WHT

985135GRY

**GTO-5 18 AWG
5000 VOLTS - 105°C
C(UL) LISTED
BLACK**

Type: This cable is constructed with one 18 AWG stranded tinned copper conductor insulated with 105C sunlight resistant polyvinyl chloride and is suitable for indoor or outdoor use for 5000 volt neon sign gas tube oil burner ignition cable applications.

*Meets the construction requirements of Underwriters Laboratories Standard UL 814 for GTO-5.
Meets the construction requirements of Canadian Standards Association C22.2 No. 127 for GTO-5.*

1.0 SPECIFICATIONS:

1.1 CONDUCTOR:

- 1.1.1 Material: Tinned Copper
- 1.1.2 Size: 18 AWG
- 1.1.3 Stranding: 19/.0092"
- 1.1.4 O.D.: .045"

1.2 DIELECTRIC:

- 1.2.1 Material: Polyvinyl Chloride
- 1.2.2 Wall Thickness: .043"
- 1.2.3 O.D.: .130" +/- .005" nom.

1.3 PRINT:

- 1.3.1 "TUF-HIDE® GTO-5 5,000V
105°C 18 AWG REV 8/99 E135239
+++ (UL) OR C(UL) GTO-5 5,000V
105°C 18 AWG"

1.4 PUT-UP:

- 1.4.1 Bulk reels or boxes per customer specifications.